

1 Identification

- **Product identifier**
- **Trade name:** SU-8 3000 Series Resists
- **Product number:** Y311075, Y311074, Y311072, Y311060, Y311049, Y311035
- **Application of the substance / the mixture** Photoresist
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Kayaku Advanced Materials, Inc.
 200 Flanders Road
 Westborough, MA 01581
 Tel: (617) 965-5511
 Fax: (617) 965-5818
- **Information department:**
 Product Safety
 Email: productsafety@kayakuam.com
- **Emergency telephone number:**
 Kayaku Advanced Materials : 617-965-5511
 Chemtrec USA Emergency : 800-424-9300
 Chemtrec International Emergency : 703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3 H226 Flammable liquid and vapor.



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Acute Toxicity - Inhalation 4 H332 Harmful if inhaled.

Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Aquatic Acute 2 H401 Toxic to aquatic life.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
(Contd. on page 2)

Printing date 04/03/2024

Reviewed on 04/03/2024

Trade name: SU-8 3000 Series Resists

(Contd. of page 1)

Hazard pictograms



GHS02 GHS07 GHS09

Signal word Warning

Hazard-determining components of labeling:

Epoxy resin

Epoxy novolac polymer

Proprietary polyglycidyl ether

Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)

Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-,(OC-6-11)-hexafluoroantimonate (1-) (1:2)

Hazard statements

H226 Flammable liquid and vapor.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

13 % of the mixture consists of component(s) of unknown toxicity.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 2
Fire = 3
Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = 2
Fire = 3
Reactivity = 0

(Contd. on page 3)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2024

Reviewed on 04/03/2024

Trade name: SU-8 3000 Series Resists

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

120-92-3	Cyclopentanone ⚠ Flammable Liquids 3, H226; ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319	15-65%
	Epoxy resin ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317	20-60%
	Cycloaliphatic Epoxy Resin ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319	5-20%
108-32-7	Propylene carbonate ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319	1-5%
	Proprietary polyglycidyl ether ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317	1-5%
71449-78-0	Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Sensitization - Skin 1, H317	0.5-2%
89452-37-9	Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-,(OC-6-11)-hexafluoroantimonate (1-) (1:2) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Sensitization - Skin 1, H317	0.5-2%
	Epoxy Compound ⚠ Eye Damage 1, H318	0.5-2%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

· **After inhalation:** Supply fresh air and to be sure call for a doctor.

· **After skin contact:**

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/03/2024

Reviewed on 04/03/2024

Trade name: SU-8 3000 Series Resists

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 - Alcohol resistant foam
 - Fire-extinguishing powder
 - Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear SCBA.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Wear protective equipment. Keep unprotected persons away.
 - Ensure adequate ventilation
 - Keep away from ignition sources
- **Environmental precautions:**
 - Do not allow product to reach sewage system or any drains.
 - Inform respective authorities in case of seepage into water course or sewage system.
 - Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Ensure adequate ventilation.
 - Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

120-92-3	Cyclopentanone	0.87 ppm
108-32-7	Propylene carbonate	34 mg/m ³
	Epoxy Compound	9.3 mg/m ³

· PAC-2:

120-92-3	Cyclopentanone	9.5 ppm
108-32-7	Propylene carbonate	370 mg/m ³
	Epoxy Compound	100 mg/m ³

· PAC-3:

120-92-3	Cyclopentanone	57 ppm
108-32-7	Propylene carbonate	2,200 mg/m ³
	Epoxy Compound	230 mg/m ³

US

(Contd. on page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2024

Reviewed on 04/03/2024

Trade name: SU-8 3000 Series Resists

(Contd. of page 4)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 - Ensure good ventilation/exhaust at the workplace.
 - Prevent formation of aerosols.
 - Keep away from heat and direct sunlight.
- **Information about protection against explosions and fires:**
 - Keep ignition sources away - Do not smoke.
 - Use explosion-proof apparatus / fittings and spark-proof tools.
 - Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and containers:**
 - Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles.
- **Information about storage in one common storage facility:**
 - Do not store together with oxidizing and acidic materials.
 - Do not store together with alkalis (caustic solutions).
 - Do not store together with amines.
- **Further information about storage conditions:**
 - Keep container well-sealed in cool, dry location.
 - Protect from heat and direct sunlight.
 - Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

89452-37-9 Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-,(OC-6-11)-hexafluoroantimonate (1-)] (1:2)	
ACGIH TLV TWA	0.5 mg/m ³
NIOSH IDLH	50 mg/m ³
OSHA PEL	0.5 mg/m ³
71449-78-0 Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)	
NIOSH IDLH	ACGIH TLV TWA: 0.5 mg/m ³
OSHA PEL	50 mg/m ³
OSHA PEL	0.5 mg/m ³

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from food and beverages.
 - Immediately remove all soiled and contaminated clothing.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/03/2024

Reviewed on 04/03/2024

Trade name: SU-8 3000 Series Resists

(Contd. of page 5)

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory equipment:

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves Nitrile rubber, NBR

· Penetration time of glove material Contact glove manufacturer for break-through time.

· Eye protection:



Tightly sealed goggles

· Body protection: Long-sleeved work clothes

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid

Color: Light yellow

Odor: Mild

Odor threshold: Not determined.

pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 130 °C (266 °F)

· Flash point: 30 °C (86 °F)

· Flammability (solid, gaseous): Not applicable.

· Auto igniting: 430 °C (806 °F)

· Decomposition temperature: Not determined.

· Ignition temperature: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower: Not determined.

Upper: Not determined.

· Vapor pressure: Not determined.

· Density: See Other information

(Contd. on page 7)

US

Printing date 04/03/2024

Reviewed on 04/03/2024

Trade name: SU-8 3000 Series Resists

(Contd. of page 6)

· Vapor density	Not determined.			
· Evaporation rate	1.6-2.3 (BuAc=1)			
· Solubility in / Miscibility with Water:	Water miscible No			
· Partition coefficient (n-octanol/water):	Not determined.			
· Viscosity: Dynamic:	Not determined.			
· Other information	Name	Number	Sp. Grav.	VOC(% by wt.)
	SU-8 3002	Y311035	1.032	65
	SU-8 3005	Y311049	1.074	50
	SU-8 3010	Y311060	1.105	39
	SU-8 3025	Y311072	1.140	27
	SU-8 3035	Y311074	1.146	25
	SU-8 3050	Y311075	1.150	23
				VOC(g/L)
				675
				530
				425
				305
				285
				265

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Exothermic polymerization.
- **Conditions to avoid**
 - Heat, flames and sparks. Extremes of temperature and direct sunlight.
 - Contact with incompatible materials.
- **Incompatible materials:** Strong Oxidizing Agents, Strong Bases, Strong Acids, Amines
- **Hazardous decomposition products:**
 - Carbon monoxide
 - Carbon dioxide
 - Danger of toxic pyrolysis products.
 - Corrosive gases/vapors

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
Epoxy resin		
Oral	LD50	>2000 mg/kg (Rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50	>5 mg/L (Rat)
Epoxy Compound		
Oral	LD50	8030 mg/kg (Rat)
Dermal	LD50	4248 mg/kg (Rat)
Inhalative	LC50/4 h	> 5.3 mg/l (Rat)

(Contd. on page 8)

us

Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2024

Reviewed on 04/03/2024

Trade name: SU-8 3000 Series Resists

(Contd. of page 7)

120-92-3 Cyclopentanone		
Oral	LD50	1820 mg/kg (Rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	19.5 mg/l (Rat)
Proprietary polyglycidyl ether		
Oral	LD50	>2000 mg/kg (Rat)
<ul style="list-style-type: none"> · Primary irritant effect: · on the skin: Irritant to skin and mucous membranes. · on the eye: Irritating effect. · Sensitization: Sensitization possible through skin contact. · Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations: Irritant · Carcinogenic categories 		
<ul style="list-style-type: none"> · IARC (International Agency for Research on Cancer) 		
None of the ingredients are listed.		
<ul style="list-style-type: none"> · NTP (National Toxicology Program) 		
None of the ingredients are listed.		
<ul style="list-style-type: none"> · OSHA-Ca (Occupational Safety & Health Administration) 		
None of the ingredients are listed.		

12 Ecological information

· Toxicity

· Aquatic toxicity:

Epoxy resin	
100<LC/EC/IC 50	≤1000 mg/l (algae) ≤1000 mg/l (fish) ≤1000 mg/l (invertebrates)
89452-37-9 Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-,(OC-6-11)-hexafluoroantimonate (1-) (1:2)	
LC50/24 h	4.4 mg/l (daphnia)
LC50/48 hr	0.68 mg/L (daphnia)
71449-78-0 Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)	
LC50/24 h	4.4 mg/l (daphnia)
LC50/48 hr	0.68 mg/L (daphnia)
Epoxy Compound	
EC50/48 h	30 mg/l (daphnia magna)
EC50/72 h	255 mg/l (Desmodesmus subspicatus (green algae))
LC50/96 h	55 mg/l (Cyprinus carpio (common carp))
120-92-3 Cyclopentanone	
EC50/48 h	3600 mg/l (Ceriodaphnia dubia (water flea)) 100 mg/l (daphnia magna)

(Contd. on page 9)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2024

Reviewed on 04/03/2024

Trade name: SU-8 3000 Series Resists

(Contd. of page 8)

EC50/72 h	>100 mg/l (<i>scenedesmus subspicatus</i>)
LC50/48 hr	2950 mg/L (<i>golden orfe</i>)
LC50/96 h	>100 mg/l (<i>fish</i>)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
 - **Bioaccumulative potential** No further relevant information available.
 - **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
 - **Remark:** Toxic for fish
 - **Additional ecological information:**
 - **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.
Disposal must be made in accordance with Federal, State, and Local regulations.
- **Uncleaned packagings:**
 - **Recommendation:** Disposal must be made in accordance with Federal, State, and Local regulations.

14 Transport information

· UN-Number	
· DOT, ADR, IMDG, IATA	UN1866
· UN proper shipping name	
· DOT	Resin solution
· ADR, IATA	RESIN SOLUTION
· IMDG	RESIN SOLUTION (Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1), Sulfonium, (thiodi-4,1- phenylene) bis[diphenyl-,(OC-6-11)-hexafluoroantimonate(1-) (1:2)), MARINE POLLUTANT

(Contd. on page 10)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/03/2024

Reviewed on 04/03/2024

Trade name: SU-8 3000 Series Resists

(Contd. of page 9)

· **Transport hazard class(es)**

· **DOT**



· **Class**

3 Flammable liquids

· **Label**

3

· **ADR, IMDG, IATA**



· **Class**

3 Flammable liquids

· **Label**

3

· **Packing group**

· **DOT, ADR, IMDG, IATA**

III

· **Environmental hazards:**

Product contains environmentally hazardous substances:
Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-)(1:1)

· **Marine pollutant:**

Yes

· **Special precautions for user**

Warning: Flammable liquids

· **Hazard identification number (Kemler code):** 30

· **EMS Number:**

F-E,S-E

· **Stowage Category**

A

· **Transport in bulk according to Annex II of**

MARPOL73/78 and the IBC Code

Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 60 L

On cargo aircraft only: 220 L

· **ADR**

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 1866 RESIN SOLUTION, 3, III

US

(Contd. on page 11)

Safety Data Sheet
 acc. to OSHA HCS

Printing date 04/03/2024

Reviewed on 04/03/2024

Trade name: SU-8 3000 Series Resists

(Contd. of page 10)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Sara**

- Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

- Section 313 (Specific toxic chemical listings):**

71449-78-0 Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)

89452-37-9 Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-,(OC-6-11)-hexafluoroantimonate (1-) (1:2)

- TSCA (Toxic Substances Control Act):** All ingredients are listed or comply with TSCA regulations.

- Hazardous Air Pollutants**

None of the ingredients are listed.

- Proposition 65**

- Chemicals known to cause cancer:**

None of the ingredients are listed.

- Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

- Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

- Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

- Carcinogenic categories**

- EPA (Environmental Protection Agency)**

None of the ingredients are listed.

- TLV (Threshold Limit Value)**

None of the ingredients are listed.

- NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

- Massachusetts State Right To Know List**

120-92-3 Cyclopentanone

- New Jersey State Right To Know List**

120-92-3 Cyclopentanone

Epoxy Compound

- Pennsylvania Hazardous Substances List**

120-92-3 Cyclopentanone

Epoxy Compound

- California SCAQMD Rule 443.1 VOC's: See Section 9**

- GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 12)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/03/2024

Reviewed on 04/03/2024

Trade name: SU-8 3000 Series Resists

(Contd. of page 11)

· Hazard pictograms



GHS02 GHS07 GHS09

· Signal word Warning

· Hazard-determining components of labeling:

Epoxy resin

Epoxy novolac polymer

Proprietary polyglycidyl ether

Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)

Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-, (OC-6-11)-hexafluoroantimonate (1-) (1:2)

· Hazard statements

H226 Flammable liquid and vapor.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuam.com)

· Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

(Contd. on page 13)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/03/2024

Reviewed on 04/03/2024

Trade name: SU-8 3000 Series Resists

(Contd. of page 12)

Date of preparation / last revision 04/03/2024 / 9**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Acute Toxicity - Inhalation 4: Acute toxicity – Category 4

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

US