The	University	of Chicago		Su	rvey Recor	d for Remo	ovable Conta	amination	(Form to	documen	t surveys to	r two weeks)	
Principal I	nvestigato	or:					Lab	Location:					
Survey Instrument: #1 Manufacturer:					Model #		Serial #						
Circle Probe(s) Used:			GM	Crystal		Circle Meter face units for F		Probe(s):	mR/hr	cpm	cps		
		#2 Manufactur	er:		·	Model #			Serial #		•	·	
Circle Probe(s) Used:				GM	Crystal		Circle Meter	r face units for		mR/hr	cpm	- cps	
· · ·				Orystai			T Idoc driits for	1 1000(3).		Орт			
Liquid Scintillation Counter: Manufacturer:					Model #			Serial #					
Gamma Counter: Manufacturer:				Model #				Serial #					
CHECK FO	OR USAGE	SINCE LAS	T DOCUM	ENTED SUF	RVEY BEF	ORE COM	IPLETING T	THE NEXT S	SURVEY			Rev. 3/2008	
												ed once per week	
		l has not been u the box to the					_			d survey, yo	ou only need	to date the surv	ey
Section, milita		E since last su					C-14	P-32	S-35	C-51	I-125	Other:	
Cumusus Anada			•		otopes used:	H-3	C-14	P-32	S-35	U-51			B. a. deal
Survey Areas: You should include hands, shoes, labcoat, workbenches, floor of work area, hood, sink, equipment used, storage units, waste storage				GM Probe*			Nal Probe* (I-125 use only)		Wipe Test (cpm)		mination Res	ults**	
containers, telephone, etc.) Indicate survey locations in these two													
columns.	In at Disa	I-	7 1				(с	pm)	(Record act	ual numbers)	(use back	for additional comm	nents)
Date (mm/dd/ax)	Inst. Bkg.		7. 3.								1		
(mm/dd/yy)	2.		9.				11				11		
	3.		10.				1				11		
Initials	4.	•	11.								11		
	5.	•	12.]		
	6.	•	13.										
	NO USAG	E since last su	rvey record	Circle is	otopes used:	H-3	C-14	P-32	S-35	C-51	l-125	Other:	
Survey Area	as: You shoul	ld include hands s	shoes lahcoat v	vorkhanchas	T						Decontai	mination Res	ulte*
Survey Areas: You should include hands, shoes, labcoat, workbenches, floor of work area, hood, sink, equipment used, storage units, waste storage							Nal Probe*		Wipe Test		Decoma	illiation ites	uits
containers, telephone, etc.) Indicate survey locations in these two				GM Probe*		(I-125 use only)		(cpm)		Constant	6	(-)	
columns. Date Inst. Bkg. 7.					(C	pm)	(Record acti	ual numbers)	(use back	for additional comm	nents)		
(mm/dd/yy)	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1		7. 3.				1				11		
(IIIII/du/yy)	2.		9.				1				11		
	3.		10.								1		
Initials	4.		11.								1		
	5.		12.][
	6.	•	13.										

^{*} A checkmark may signify a background (Bkg) reading. Readings above Bkg must be recorded as numerical values. The "Inst. Bkg." reading must be a numerical value.

^{**} The following survey results require further evaluation and corrective actions: 1) Wipe test > 400 cpm; 2) GM survey instrument reading > 0.25 mR/hr, 600 cpm (6 cps for Mini Monitors and Rad-Monitors that read in cps); 3) Nal survey instrument reading > 1000 cpm.

^{***} Please note: Any contamination found that is removable from any surface must be cleaned no matter what the survey instrument is reading. Even if the survey instrument reading is above Bkg, but below the action levels noted above.